

DataSheet

Market-leading Commander® has something new to offer – CommanderEDGE. BS EN3 Kitemark approved across the range, this range has become the choice of the professional, with a reassuring mixture of performance, quality and value. The range includes Water, Foam, CO₂ and Powder models and offers solutions for almost all situations. The internationallyrecognised BS Kitemark is assurance of dependable design and manufacture.



CO₂ FIRE EXTINGUISHERS

Suitable for both electrical and flammable liquid fires, CO₂ is non-damaging to electrical equipment and machinery. The CommanderEDGE product is probably the most robust CO² fire extinguisher available in the UK. The cylinder is made from an alloy/steel mix making the perfect combination of strength and a pleasing aesthetic appearance. This is a true leader for the industry. The 5kg model compes with an 89B fire rating probably the highest available in the UK. Supplied with nonconductive discharge horns, these extinguishers are ideal for workshop, industrial and office environments

Technical Specification	CO2E	CO5E
Capacity	2kg	5kg
Fire Rating	34B	89B
Extinguishing Medium	CO ₂	CO ₂
Working Pressure	56 bar @ 20°C	56 bar @ 20°C
Temperature Range	-20-+60°C	-20-+60°C
Cylinder Material	Alloy Steel	Alloy Steel
Pressuring Gas	_	-

COMMANDER EDGE

PRODUCT CODE

CO2E | CO5E

PRODUCT GROUP

CommanderEDGE Extinguishers

DIMENSIONS (mm) (height x width x diameter)

CO2E: 585 x 165 x 105 CO5E: 760 x 180 x 140

WEIGHT

CO2E: 6.95kg CO5E: 14.5kg

- Kitemarked to BS EN3
- Full range of spare parts available
- Corrosion-resistant finish
- 5-year warranty
- Supplied with safe horn/hose & horn



029 2086 8333



029 2085 0627



sales@checkfire.co.uk



www.CheckFire.co.uk







