

DataSheet

Market-leading Commander[®] has something new to offer – CommanderEDGE. BS EN3 Kitemark approved across the range, this range has become the choice of the professional, with a reassuring mixture of performance, quality and value. The range includes Water, Foam, CO_2 and Powder models and offers solutions for almost all situations. The internationallyrecognised BS Kitemark is assurance of dependable design and manufacture.



WATER FIRE EXTINGUISHERS

Water extinguishers still remain a popular choice for Class A fire risks. This model is Kitemarked and comes complete with a plastic base skirt for protection. Both models have passed the 35kVa Dielectric test and comply fully with BS EN3-7: 2004 Clause 9 - Dielectric test for water-based extinguishers. All CommanderEDGE extinguishers are screen printed and come with a 5-year warranty. Water – the economical, reliable choice for Class A fires.

Technical Specification	WS6E	WS6EA	WS9E
Capacity	6 litre	6 litre	9 litre
Fire Rating	13A	34A	13A
Extinguishing Medium	Demineralised water	Water + additive	Water
Working Pressure	15 bar at temp 20°C	12 bar	14 bar
Temperature Range	+5°-+60°C	-10°C-+60°C with suitable cover	+5°-+60°C
Cylinder Material	Steel	Steel	Steel
Pressuring Gas	Nitrogen	Nitrogen	Nitrogen

029 2086 8333

29 2080 8555

sales@checkfire.co.uk

www.CheckFire.co.uk

029 2085 0627

C@MMANDER EDGE

PRODUCT CODE WS6E | WS6EA | WS9E

PRODUCT GROUP CommanderEDGE Extinguishers

DIMENSIONS (mm) (height x width x diameter) WS6E: 502 x 197x 160 WS6EA: 550 x 310 x 165 WS9E: 620 x 330 x 185

WEIGHT

WS6E: 9.9kg WS6EA: 10kg WS9E: 14.2kg

- Kitemarked to BS EN3
- Manufactured in Europe*
- Full range of spare parts available
- Corrosion-resistant finish
- 5-year warranty
- Plastic base skirt for protection
- Polyethylene internal lining
- 35kVa Dielectric test certified

*WS6E model only

